


PHYSICAL PROPERTIES

Boiling Temperature	516.4°F
Flash Point	279°F
Melting Point	82°F

PRODUCT SPECIFICATIONS	VALUE	TEST METHOD
Assay	Mín. 99.30 %	GC
Monoethanolamine	Máx. 0.30 %	GC
Triethanolamine	Máx. 0.30 %	GC
Water	Máx. 0.10 %	DIN 51777
Colour	Máx. 20 APHA	DIN EN 1557

Formula:



Formula Weight: 105.137g/mol

CAS Registry: 111-42-2

Storage & Handling

Precautions for safe handling:

Good ventilation of the warehouse and work areas. Handle in accordance with the regulations for chemical products. Do not eat, drink or smoke during use. Wash up hands and / or face before breaks and at the end of work.

Protection against fire / explosion:

Avoid accumulation of electrostatic charges. Keep away from sources of ignition. Extinguisher accessible.

Conditions for safe storage, including any incompatibilities:

Separate from acids and acid forming substances. Suitable materials: Carbon Steel, Stainless Steel 1.4401 (V4), Stainless Steel 1.4301 (V2), High Density Polyethylene (HDPE), Low Density Polyethylene (LDPE), Tin (Tinplate), Crystal.

Documento Versión Web / Estimado Cliente: Antes de realizar su compra solicite la última versión de este documento.